

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

**APPLICATION FOR UNITED STATES PATENT**

**VEHICLE BASED DATA COLLECTION AND PROCESSING SYSTEM**

**INVENTORS:**

Chester L. Smitherman  
9147 Cardwell Drive  
Houston, Texas 77055  
Citizen of USA

Leo J. Peters III  
129 Phantum  
Bellaire, Texas 77401  
Citizen of USA

Tuy Vu Mai  
13314 Misty Mill Drive  
Houston, Texas 77041  
Citizen of USA

Via Express Mail EV 322135555 US on September 18, 2003

## **VEHICLE BASED DATA COLLECTION AND PROCESSING SYSTEM**

### **CROSS-REFERENCE TO RELATED APPLICATION**

5   **[0001]**   Applicants claim priority to United States Provisional Patent Application Serial No. 60/412,504 filed September 20, 2002 for “Vehicle Based Data Collection and Processing System.”

### **TECHNICAL FIELD OF THE INVENTION**

10   **[0002]**   The present invention relates, generally, to the field of remote imaging techniques and, more particularly, to a system for rendering high-resolution, high accuracy, low distortion digital images over very large fields of view.

### **BACKGROUND OF THE INVENTION**

15   **[0003]**   Remote sensing and imaging are broad-based technologies having a number of diverse and extremely important practical applications - such as geological mapping and analysis, military surveillance and planning, and meteorological forecasting. Aerial and satellite-based photography and imaging are especially useful remote imaging techniques that have, over recent years, become heavily reliant on the collection and processing of digital image, spectral, spatial, elevation, and vehicle location and orientation data. Spatial data - characterizing real estate  
20   improvements and locations, roads and highways, environmental hazards and conditions, utilities infrastructures (e.g., phone lines, pipelines), and geophysical features - can now be collected,

processed, and communicated in a digital format to conveniently provide highly accurate mapping and surveillance data for various applications (e.g., dynamic GPS mapping). Elevation data may be used to improve the overall system's spatial and positional accuracy and may be acquired from either existing Digital Elevation Model (DEM) data sets or collected with the  
5 spectral sensor data from an active, radiation measuring Doppler based devices, or passive, stereographic calculations.

[0004] Major challenges facing some such remote sensing and imaging applications are spatial resolution and spectral fidelity. Photographic issues, such as spherical aberrations, astigmatism, field curvature, coma, distortion, and chromatic aberrations are well known problems that must  
10 be dealt with in any sensor/imaging application. Certain applications require very high image resolution – often with tolerances of inches. Depending upon the particular system used (e.g., aircraft, satellite, or space vehicle), an actual digital imaging device may be located anywhere from several feet to miles from its target, resulting in a very large scale factor. Providing images with very large scale factors, that also have resolution tolerances of inches, poses a challenge to  
15 even the most robust imaging system. Thus, conventional systems usually must make some trade-off between resolution quality and the size of a target area that can be imaged. If the system is designed to provide high-resolution digital images, then the field of view (FOV) of the imaging device is typically small. If the system provides a larger FOV, then usually the resolution of the spectral and spatial data is decreased and distortions are increased.

20 [0005] Ortho-imaging is an approach that has been used in an attempt to address this problem. In general, ortho-imaging imaging renders a composite image of a target by compiling varying

sub-images of the target. Typically, in aerial imaging applications, a digital imaging device that has a finite range and resolution records images of fixed subsections of a target area sequentially. Those images are then aligned according to some sequence to render a composite of a target area.

5 [0006] Often, such rendering processes are very time-consuming and labor intensive. In many cases, those processes require iterative processing that measurably degrades image quality and resolution – especially in cases where thousands of sub-images are being rendered. In cases where the imaging data can be processed automatically, that data is often repetitively transformed and sampled – reducing color fidelity and image sharpness with each successive  
10 manipulation. If automated correction or balancing systems are employed, such systems may be susceptible to image anomalies (e.g., unusually bright or dark objects) – leading to over or under-corrections and unreliable interpretations of image data. In cases where manual rendering of images is required or desired, time and labor costs are immense.

[0007] There is, therefore, a need for an ortho-image rendering system that provides efficient  
15 and versatile imaging for very large FOVs and associated data sets, while maintaining image quality, accuracy, positional accuracy and clarity. Additionally, automation algorithms are applied extensively in every phase of the planning, collecting, navigating, and processing all related operations.

## SUMMARY OF THE INVENTION

[0008] The present invention relates to a vehicle data collection and processing system using remote sensors. The system may include computer console units that control vehicle and system operations in real-time. The system may also include global positioning systems that are linked to and communicate with the computer consoles. Additionally, cameras and/or camera array assemblies can be employed for producing an image of a target viewed through an aperture. The camera array assemblies are communicatively connected to the computer consoles. The camera array assembly has a mount housing, a first imaging sensor centrally coupled to the housing having a first focal axis passing through the aperture. The camera array assembly also has a second imaging sensor coupled to the housing and offset from the first imaging sensor along an axis, that has a second focal axis passing through the aperture and intersecting the first focal axis within an intersection area. The camera array assembly has a third imaging sensor, coupled to the housing and offset from the first imaging sensor along the axis, opposite the second imaging sensor, that has a third focal axis passing through the aperture and intersecting the first focal axis within the intersection area. Any number of one-to-n cameras may be used in this manner, where n can be any odd or even number.

[0009] The system may also include an Attitude Measurement Unit (AMU) such as inertial, optical, or similar measurement units communicatively connected to the computer consoles and the camera array assemblies. The AMU may determine the yaw, pitch, and/or roll of the aircraft at any instant in time and successive DGPS positions may be used to measure the vehicle heading with relation to geodesic north. The AMU data is integrated with the precision DGPS

data to produce a robust, real-time AMU system. The system may further include a mosaicing module housed within the computer consoles. The mosaicing module includes a first component for performing initial processing on an input image. The mosaicing module also includes a second component for determining geographical boundaries of an input image with the second component being cooperatively engaged with the first component. The mosaicing module further includes a third component for mapping an input image into the composite image with accurate geographical position. The third component being cooperatively engaged with the first and second components. A fourth component is also included in the mosaicing module for balancing color of the input images mapped into the composite image. The fourth component can be cooperatively engaged with the first, second and third components. Additionally, the mosaicing module can include a fifth component for blending borders between adjacent input images mapped into the composite image. The fifth component being cooperatively engaged with the first, second, third and fourth components.

**[0010]** A sixth component, an optional forward oblique and/or optional rear oblique camera array system may be implemented that collects oblique image data and merges the image data with attitude and positional measurements in order to create a digital elevation model using stereographic techniques. Creation of which may be performed in real-time onboard the vehicle or post processed later. This sixth component works cooperatively with the other components. All components may be mounted to a rigid platform for the purpose of providing co-registration of sensor data. Vibrations, turbulence, and other forces may act on the vehicle in such a way as to create errors in the alignment relationship between sensors. Utilization of common, rigid

platform mount for the sensors provides a significant advantage over other systems that do not use this co-registration architecture.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0011] For a better understanding of the invention, and to show by way of example how the same may be carried into effect, reference is now made to the detailed description of the invention along with the accompanying figures in which corresponding numerals in the different figures refer to corresponding parts and in which:

FIGURE 1 illustrates a vehicle based data collection and processing system of the present invention;

FIGURE 2 illustrates a vehicle based data collection and processing system of FIGURE 1 with the camera array assembly of the present invention shown in more detail;

FIGURE 3 illustrates a camera array assembly in accordance with certain aspects of the present invention;

FIGURE 4 illustrates one embodiment of an imaging pattern retrieved by the camera array assembly of Figure 1;

FIGURE 5 depicts an imaging pattern illustrating certain aspects of the present invention;

FIGURE 6 illustrates an image strip in accordance with the present invention;

FIGURE 7 illustrates another embodiment of an image strip in accordance with the present invention;

FIGURE 8 illustrates one embodiment of an imaging process in accordance with the present invention;

FIGURE 9 illustrates diagrammatically how photos taken with the camera array assembly can be aligned to make an individual frame;

5       FIGURE 10 is a block diagram of the processing logic according to certain embodiments of the present invention;

FIGURE 11 is an illustration of lateral oversampling looking down from a vehicle according to certain embodiments of the present invention;

10       FIGURE 12 is an illustration of lateral oversampling looking down from a vehicle according to certain embodiments of the present invention;

FIGURE 13 is an illustration of flight line oversampling looking down from a vehicle according to certain embodiments of the present invention;

FIGURE 14 is an illustration of flight line oversampling looking down from a vehicle according to certain embodiments of the present invention;

15       FIGURE 15 is an illustration of progressive magnification looking down from a vehicle according to certain embodiments of the present invention;

FIGURE 16 is an illustration of progressive magnification looking down from a vehicle according to certain embodiments of the present invention;

20       FIGURE 17 is an illustration of progressive magnification looking down from a vehicle according to certain embodiments of the present invention; and

FIGURE 18 is a schematic of the system architecture according to certain embodiments of the present invention.

#### DETAILED DESCRIPTION OF THE INVENTION

5   **[0012]** While the making and using of various embodiments of the present invention are discussed in detail below, it should be appreciated that the present invention provides many applicable inventive concepts, which can be embodied in a wide variety of specific contexts. The specific embodiments discussed herein are merely illustrative of specific ways to make and use the invention and do not limit the scope of the invention.

10   **[0013]** A vehicle based data collection and processing system 100 of the present invention is shown in Figure 1. Additional aspects and embodiments of the present invention are shown in Figures 2 and 18. System 100 includes one or more computer consoles 102. The computer consoles contain one or more computers 104 for controlling both vehicle and system operations. Examples of the functions of the computer console are the controlling digital color sensor

15   systems that can be associated with the data collection and processing system, providing the display data to a pilot, coordinating the satellite generated GPS pulse-per-second (PPS) event trigger (which may be 20 or more pulses per second), data logging, sensor control and adjustment, checking and alarming for error events, recording and indexing photos, storing and processing data, flight planning capability that automates the navigation of the vehicle, data, and

20   providing a real-time display of pertinent information. A communications interface between the control computer console and the vehicle autopilot control provides the ability to actually control the flight path of the vehicle in real-time. This results in a more precise control of the vehicle's

path than is possible by a human being. All of these functions can be accomplished by the use of various computer programs that are synchronized to the GPS PPS signals and take into account the various electrical latencies of the measurement devices.

[0014] One or more differential global positioning systems 106 are incorporated into the system 100. The global positioning systems 106 are used to navigate and determine precise flights paths during vehicle and system operations. To accomplish this, the global positioning systems 106 are communicatively linked to the computer console 102 such that the information from the global positioning systems 106 can be acquired and processed without flight interruption. Zero or more GPS units may be located at known survey points in order to provide a record of each sub-seconds' GPS satellite-based errors in order to be able to back correct the accuracy of the system 100. GPS and/or ground based positioning services may be used that eliminate the need for ground control points altogether. This technique results in greatly improved, sub-second by sub-second positional accuracy of the data capture vehicle.

[0015] One or more AMUs 108 that provide real-time yaw, pitch, and roll information that is used to accurately determine the attitude of the vehicle at the instant of data capture are also communicatively linked to the computer console 102. The present attitude measurement unit (AMU) (e.g. Applanix POS AV), uses three high performance fiber optic gyros, one gyro each for yaw, pitch, and roll measurement. AMUs from other manufacturers, and AMUs that use other inertial measurement devices can be used as well. Additionally, an AMU may be employed to determine the instantaneous attitude of the vehicle and make the system more fault tolerant to statistical errors in AMU readings. Connected to the AMU can be one or more multi-

frequency DGPS receivers 110. The multi-frequency DGPS receivers 110 can be integrated with the AMU's yaw, pitch, and roll attitude data in order to more accurately determine the location of the remote sensor platform in three dimensional space. Additionally, the direction of geodesic North may be determined by the vector created by successive DGPS positions, recorded in a  
5   synchronized manner with the GPS PPS signals.

[0016]   One or more one or more camera array assemblies 112 for producing an image of a target viewed through an aperture are also communicatively connected to the one or more computer consoles 102. The camera array assemblies 112, which will be described in greater detail below, provide the data collection and processing system with the ability to capture high  
10   resolution, high precision progressive scan or line scan, color digital photography.

[0017]   The system may also include DC power and conditioning equipment 114 to condition DC power and to invert DC power to AC power in order to provide electrical power for the system. The system may further include a navigational display 116, which graphically renders the position of the vehicle versus the flight plan for use by the pilot (either onboard or remote) of  
15   the vehicle to enable precision flight paths in horizontal and vertical planes. The system may also include an EMU module comprised of LIDAR, SAR 118 or a forward and rear oblique camera array for capturing three dimensional elevation/relief data. The EMU module 118 can include a laser unit 120, an EMU control unit 122, and an EMU control computer 124. Temperature controlling devices, such as solid state cooling modules, can also be deployed as  
20   needed in order to provide the proper thermal environment for the system.

[0018] The system also includes a mosaicing module, not depicted, housed with the computer console 102. The mosaicing module, which will be described in further detail below, provides the system the ability to gather data acquired by the global positioning system 106, the AMU 108, and the camera system 112 and process that data into useable orthomaps.

5 [0019] The system 100 also can include a Self-Locking flight pattern technique that provides the ability to micro-correct the positional accuracy of adjacent flight paths in order to realize precision that exceeds the native precision of the AMU and DGPS sensors alone.

[0020] A complete flight planning methodology is used to micro plan all aspects of missions. The inputs are the various mission parameters (latitude/longitude, resolution, color, accuracy,  
10 etc.) and the outputs are detailed on-line digital maps and data files that are stored onboard the data collection vehicle and used for real-time navigation and alarms. The ability to interface the flight planning data directly into the autopilot is an additional integrated capability. A computer program may be used that automatically controls the flight path, attitude adjustments, graphical display, moving maps of the vehicle path, checks for alarm conditions and corrective actions,  
15 notifies the pilot and/or crew of overall system status, and provides for fail-safe operations and controls. Safe operations parameters may be constantly monitored and reported. Whereas the current system uses a manned crew, the system is designed to perform equally well in an unmanned vehicle.

[0021] Figure 2 shows another depiction of the present invention. In Figure 2, the camera  
20 array assembly 112 is shown in more detail. As is shown, the camera array assembly 112 allows

for images to be acquired from the rear oblique, the forward obliques and the nadir positions. Figure 3, describes in more detail a camera array assembly of the present invention. Figure 3 provides a camera array assembly 300 airborne over target 302 (e.g., terrain). For illustrative purposes, the relative size of assembly 300, and the relative distance between it and terrain 302, are not depicted to scale in Figure 3. The camera array assembly 300 comprises a housing 304 within which imaging sensors 306, 308, 310, 312 and 314 are disposed along a concave curvilinear axis 316. The radius of curvature of axis 316 may vary or be altered dramatically, providing the ability to effect very subtle or very drastic degrees of concavity in axis 316. Alternatively, axis 316 may be completely linear – having no curvature at all. The imaging sensors 306, 308, 310, 312 and 314 couple to the housing 304, either directly or indirectly, by attachment members 318. Attachment members 318 may comprise a number of fixed or dynamic, permanent or temporary, connective apparatus. For example, the attachment members 318 may comprise simple welds, removable clamping devices, or electro-mechanically controlled universal joints.

[0022] Additionally, the system 100 may have a real-time, onboard navigation system to provide a visual, bio-feedback display to the vehicle pilot, or remote display in the case of operations in an unmanned vehicle. The pilot is able to adjust the position of the vehicle in real-time in order to provide a more accurate flight path. The pilot may be onboard the vehicle or remotely located and using the flight display to control the vehicle through a communication link.

[0023] The system 100 may also use highly fault-tolerant methods been developed that provides a software inter-leaved disk storage methodology that allows one or two hard drives to fail and still not lose target data that is stored on the drives. This software inter-leaved disk storage methodology provides superior fault-tolerance and portability versus other, hardware  
5 methodologies, such as RAID-5.

[0024] The system 100 may also incorporate a methodology that has been developed that allows for a short calibration step just before mission data capture. The calibration methodology step adjusts the camera settings, mainly exposure time, based on sampling the ambient light intensity and setting near optimal values just before reaching the region of interest. A moving  
10 average algorithm is then used to make second-by-second camera adjustments in order to deliver improved, consistent photo results. This improves the color processing of the orthomaps. Additionally, the calibration may be used to check or to establish the exact spatial position of each sensor device (cameras, DPG, AMU, EMU, etc.). In this manner, changes that may happen in the spatial location of these devices may be accounted for and maintain overall system  
15 precision metrics.

[0025] Additionally, the system 100 may incorporate a methodology that has been developed that allows for calibrating the precision position and attitude of each sensor device (cameras, DPG, AMU, EMU, etc.) on the vehicle by flying over an area that contains multiple known, visible, highly accurate geographic positions. A program takes this data as input and outputs the  
20 micro positional data that is then used to precisely process the orthomaps.

[0026] As depicted in Figure 3, housing 304 comprises a simple enclosure inside of which imaging sensors 306, 308, 310, 312 and 314 are disposed. Whereas Figure 3 depicts a 5-camera array, the system works equally well when utilizing any number of camera sensors from 1 to any number. Sensors 306 – 314 couple, via the attachment members 318, either collectively to a single transverse cross member, or individually to lateral cross members disposed between opposing walls of the housing 304. In alternative embodiments, the housing 304 may itself comprise only a supporting cross member of concave curvature to which the imaging sensors 306 through 314 couple, via members 318. In other embodiments, the housing 304 may comprise a hybrid combination of enclosure and supporting cross member. The housing 304 further comprises an aperture 320 formed in its surface, between the imaging sensors and target 302. Depending upon the specific type of host craft, the aperture 320 may comprise only a void, or it may comprise a protective screen or window to maintain environmental integrity within the housing 304. In the event that a protective transparent plate is used for any sensor, special coatings may be applied to the plate to improve the quality of the sensor data. Optionally, the aperture 320 may comprise a lens or other optical device to enhance or alter the nature of the images recorded by the sensors. The aperture 320 is formed with a size and shape sufficient to provide the imaging sensors 306 through 314 proper lines of sight to a target region 322 on terrain 302.

[0027] The imaging sensors 306 through 314 are disposed within or along housing 304 such that the focal axes of all sensors converge and intersect each other within an intersection area bounded by the aperture 320. Depending upon the type of image data being collected, the

specific imaging sensors used, and other optics or equipment employed, it may be necessary or desirable to offset the intersection area or point of convergence above or below the aperture 320. The imaging sensors 306 through 314 are separated from each other at angular intervals. The exact angle of displacement between the imaging sensors may vary widely depending upon the number of imaging sensors utilized and on the type of imaging data being collected. The angular displacement between the imaging sensors may also be unequal, if required, so as to provide a desired image offset or alignment. Depending upon the number of imaging sensors utilized, and the particular configuration of the array, the focal axes of all imaging sensors may intersect at exactly the same point, or may intersect at a plurality of points, all within close proximity to each other and within the intersection area defined by the aperture 320.

[0028] As depicted in Figure 3, the imaging sensor 310 is centrally disposed within the housing 304 along axis 316. The imaging sensor 310 has a focal axis 324, directed orthogonally from the housing 304 to align the line of sight of the imaging sensor with the image area 326 of the region 322. The imaging sensor 308 is disposed within the housing 304 along the axis 316, adjacent to the imaging sensor 310. The imaging sensor 308 is aligned such that its line of sight coincides with the image area 328 of the region 322, and such that its focal axis 330 converges with and intersects the axis 324 within the area bounded by the aperture 320. The imaging sensor 312 is disposed within the housing 304 adjacent to the imaging sensor 310, on the opposite side of the axis 316 as the imaging sensor 308. The imaging sensor 312 is aligned such that its line of sight coincides with the image area 332 of the region 322, and such that its focal axis 334 converges with and intersects axes 324 and 330 within the area bounded by the aperture

320. The imaging sensor 306 is disposed within the housing 304 along the axis 316, adjacent to the sensor 308. The imaging sensor 306 is aligned such that its line of sight coincides with the image area 336 of region 322, and such that its focal axis 338 converges with and intersects the other focal axes within the area bounded by aperture 320. The imaging sensor 314 is disposed  
5 within housing 304 adjacent to sensor 312, on the opposite side of axis 316 as sensor 306. The imaging sensor 314 is aligned such that its line of sight coincides with image area 340 of region 322, and such that its focal axis 344 converges with and intersects the other focal axes within the area bounded by aperture 320.

[0029] The imaging sensors 306 through 314 may comprise a number of digital imaging  
10 devices including, for example, individual area scan cameras, line scan cameras, infrared sensors, hyperspectral and/or seismic sensors. Each sensor may comprise an individual imaging device, or may itself comprise an imaging array. The imaging sensors 306 through 314 may all be of a homogenous nature, or may comprise a combination of varied imaging devices. For ease of reference, the imaging sensors 306 through 314 are hereafter referred to as cameras 306  
15 through 314, respectively.

[0030] In large-format film or digital cameras, lens distortion is typically a source of imaging problems. Each individual lens must be carefully calibrated to determine precise distortion factors. In one embodiment of this invention, small-format digital cameras having lens angle widths of 17 degrees or smaller are utilized. This alleviates noticeable distortion efficiently and  
20 affordably.

[0031] Cameras 306 through 314 are alternately disposed within housing 304 along axis 316 such that each camera's focal axis converges upon aperture 320, crosses focal axis 324, and aligns its field of view with a target area opposite its respective position in the array resulting in a "cross-eyed", retinal relationship between the cameras and the imaging target(s). The camera array assembly 300 is configured such that adjoining borders of image areas 326, 328, 332, 336 and 340 overlap slightly.

[0032] If the attachment members 318 are of a permanent and fixed nature (e.g., welds), then the spatial relationship between aperture 320, the cameras, and their lines of sight remain fixed as will the spatial relationship between image areas 326, 328, 332, 336 and 340. Such a configuration may be desirable in, for example, a satellite surveillance application where the camera array assembly 300 will remain at an essentially fixed distance from region 322. The position and alignment of the cameras is set such that areas 326, 328, 332, 336 and 340 provide full imaging coverage of region 322. If the attachment members 318 are of a temporary or adjustable nature, however, it may be desirable to selectively adjust, either manually or by remote automation, the position or alignment of the cameras so as to shift, narrow or widen areas 326, 328, 332, 336 and 340 – thereby enhancing or altering the quality of images collected by the camera array assembly 300.

[0033] Camera 310 is designated as the principal camera. The image plane 326 of camera 310 serves as a plane of reference. The orientations of the other cameras 306, 308, 312 and 314 are measured relative to the plane of reference. The relative orientations of each camera are

measured in terms of the yaw, pitch and roll angles required to rotate the image plane of the camera to become parallel to the plane of reference. The order of rotations is roll, pitch and yaw.

[0034] Referring now to Figure 2, images of areas 336, 328, 326, 332 and 340 taken by cameras 306 through 314, respectively, are illustrated from an overhead view. Again, because of the “cross-eyed” arrangement, the image of area 336 is taken by camera 306, the image of area 340 is taken by camera 314, and so on. In one embodiment of the present invention, images other than those taken by the center camera 310 take on a trapezoidal shape after perspective transformation. Cameras 306 through 314 form an array along axis 316 that is, in most applications, pointed down vertically. In an alternative embodiment, a second array of cameras, configured similar the array of cameras 306 through 314, is aligned with respect to the first array of cameras to have an oblique view providing a “heads-up” perspective. The angle of declination from horizontal of the heads-up camera array assembly may vary due to mission objectives and parameters but angles of 25-45 degrees are typical. Other alternative embodiments, varying the mounting of camera arrays, are similarly comprehended by the present invention. In all such embodiments, the relative positions and attitudes of the cameras are precisely measured and calibrated so as to facilitate image processing in accordance with the present invention.

[0035] In one embodiment of the present invention, an external mechanism (e.g., a GPS timing signal) is used to trigger the cameras simultaneously thereby capturing an array of input images. A mosaicing module then renders the individual input images from such an array into an ortho-rectified compound image (or “mosaic”), without any visible seams between the

adjacent images. The mosaicing module performs a set of tasks comprising: determining the geographical boundaries and dimensions of each input image; projecting each input image onto the mosaic with accurate geographical positioning; balancing the color of the images in the mosaic; and blending adjacent input images at their shared seams. The exact order of the tasks performed may vary, depending upon the size and nature of the input image data. In certain embodiments, the mosaicing module performs only a single transformation to an original input image during mosaicing. That transformation can be represented by a  $4 \times 4$  matrix. By combining multiple transformation matrices into a single matrix, processing time is reduced and original input image sharpness is retained.

[0036] During mapping of the input images to the mosaic, especially when mosaicing is performed at high resolutions, pixels in the mosaic (i.e., output pixels) may not be mapped to by any pixels in the input images (i.e., input pixels). Warped lines could potentially result as artifacts in the mosaic. Certain embodiments of the present invention overcome this with a super-sampling system, where each input and output pixel is further divided into an  $n \times m$  grid of sub-pixels. Transformation is performed from sub-pixels to sub-pixels. The final value of an output pixel is the average value of its sub-pixels for which there is a corresponding input sub-pixel. Larger  $n$  and  $m$  values produce mosaics of higher resolution, but do require extra processing time.

[0037] During its processing of image data, the mosaicing module may utilize the following information: the spatial position (e.g.,  $x$ ,  $y$ ,  $z$  coordinates) of each camera's focal point at the time an input image is captured; the attitude (i.e., yaw, pitch, roll) of each camera's image plane

relative to the target region's ground plane at the time an input image was captured; each camera's fields of view (i.e., along track and cross track); and the Digital Terrain Model (DTM) of the area. The attitude can be provided by the AMUs associated with the system. Digital terrain models (DTMs) or Digital surface models (DSMs) can be created from information  
5 obtained using a LIDAR module 118. LIDAR is similar to the more familiar radar, and can be thought of as laser radar. In radar, radio waves are transmitted into the atmosphere that scatters some of the energy back to the radar's receiver. LIDAR also transmits and receives electromagnetic radiation, but at a higher frequency since it operates in the ultraviolet, visible and infrared region of the electromagnetic spectrum. In operation, LIDAR transmits light out to  
10 a target area. The transmitted light interacts with and is changed by the target area. Some of this light is reflected / scattered back to the LIDAR instrument where it can be analyzed. The change in the properties of the light enables some property of the target area to be determined. The time for the light to travel out to the target area and back to LIDAR device is used to determine the range to the target.

15 [0038] DTM and DSM data sets can also be captured from the camera array assembly. Traditional means of obtaining elevation data may also be used such as stereographic techniques.

[0039] There are presently three basic types of LIDAR: Range finders, Differential Absorption LIDAR (DIAL) and Doppler LIDAR. Range finder LIDAR is the simplest LIDAR and is used to measure the distance from the LIDAR device to a solid or hard target. DIAL LIDAR is used  
20 to measure chemical concentrations (such as ozone, water vapor, pollutants) in the atmosphere. A DIAL LIDAR uses two different laser wavelengths that are selected so that one of the

wavelengths is absorbed by the molecule of interest while the other wavelength is not. The difference in intensity of the two return signals can be used to deduce the concentration of the molecule being investigated. Doppler LIDAR is used to measure the velocity of a target. When the light transmitted from the LIDAR hits a target moving towards or away from the LIDAR, the wavelength of the light reflected/scattered off the target will be changed slightly. This is known as a Doppler-shift and therefore Doppler LIDAR. If the target is moving away from the LIDAR, the return light will have a longer wavelength (sometimes referred to as a red shift), if moving towards the LIDAR the return light will be at a shorter wavelength (blue shifted). The target can be either a hard target or an atmospheric target (e.g. microscopic dust and aerosol particles that are carried by the wind.

[0040] A camera's focal point is used as a perspective transformation center. Its position in space is determined, for example, by a multi-frequency carrier phase post-processed GPS system mounted on the host craft. The offsets, in three dimensions, of a camera's focal point must be carefully measured against the center of the GPS antenna. These offsets are combined with the position of the GPS antenna, and the orientation of the host craft, to determine the exact position of the camera's focal point. The position of the GPS antenna is determined by post-flight processing of collected GPS data against similar ground-based GPS antennas deployed at precisely surveyed points.

[0041] One or more AMUs (e.g., the Applanix POS AV) are mounted onboard for attitude determination. The attitude of the AMU reference plane relative to the target region's ground plane is measured and recorded at short intervals, with accuracy better than one-hundredth of one

degree. The attitude of the AMU reference plane is defined as the series of rotations that can be performed on the axes of this plane to make it parallel to the ground plane. The term “align” is also used to describe this operation.

[0042] The attitude of center camera 310 (i.e. its image plane), relative to the AMU, must be  
5 carefully calibrated. The attitude of each of the other cameras, relative to center camera 310, must also be carefully calibrated. This dependent calibration is more efficient than directly calibrating each camera. When the camera array assembly 300 is remounted, only center camera 310 needs to be recalibrated. Effectively, a series of two transformations is applied to an input image from center camera 310. First, the center camera’s image plane is aligned to the AMU  
10 plane. Then, the AMU plane is aligned again to the ground plane. These transformations, however, combine into a single operation by multiplying their respective transformation matrices. For images from each of the other cameras, an additional transformation is first performed to align it with the center camera’s image plane.

[0043] The position of the focal point of center camera 310 is determined as described above.  
15 The x and y components of this position determine the position of the mosaic’s nadir point 400 on the ground. Field of view (FOV) angles of each camera are known, thus the dimensions of each input image can be determined by the z component of that camera’s focal point. An average elevation of the ground is determined by computing the average elevation of points in the DTMs of the area, and then each input image is projected to an imaginary horizontal plane at  
20 this elevation. Relief displacement is then applied using the DTMs of the area. The DTMs can be obtained from many sources including: the USGS 30- or 10-meter DTMs available for most

of the US; commercial DTMs; or DTMs obtained by a LIDAR or SAR EMU device mounted on the host craft that captures data concurrently with the cameras.

[0044] Besides being geographically correctly placed, the resulting compound image also needs to have color consistency throughout, and no visible seams at the joints between two adjacent images. The present invention provides a number of techniques for achieving this goal.

[0045] A characteristic of a conventional camera is the exposure time (i.e., the time the shutter is open to collect light onto the image plane). The longer the exposure time, the lighter the resultant image becomes. Exposure time must adapt to changes in ambient lighting caused by conditions such as: cloud coverage; the angle and position of the sun relative to the camera; and so forth. Optimal exposure time may also depend on a camera's orientation with respect to lighting sources (e.g., cameras pointing towards a sunlit object typically receive more ambient light than those pointing towards a shaded object). Exposure time is adjusted to keep the average intensity of an image within a certain desired range. For example, in 24-bit color images each Red, Green and Blue component can have intensity values from 0 to 255. In most instances, however, it is desirable to keep the average intensity at a mean value (i.e., 127).

[0046] In the present invention, an exposure control module controls exposure time for each of the cameras or imaging sensors. It examines each input image and calculates average image intensity. Based on a moving average (i.e., average intensity of the last  $X$  number of images), the exposure control module determines whether to increase or decrease exposure time. The module can use a longer running average to effect a slower reaction to changes in lighting conditions,

with less susceptibility to unusually dark or light images (e.g., asphalt roads or water). The exposure control module controls exposure time for each camera separately.

[0047] In systems where cameras are mounted without forward-motion compensation mechanisms, there must be a maximum limit for exposure time. Setting exposure time to a value larger than the maximum may cause motion-induced blurriness. For example, assume cameras are mounted on an airplane traveling at 170 miles/hour (or about 3 inches/ms). Assume desired pixel resolution is 6 inches. Forward motion during image capture should be limited to half a pixel size – which in this case equals 3 inches. Thus, maximum exposure for example is 1 millisecond.

[0048] In controlling imaging quality, it is useful to be able to determine if changes in light intensity are caused either due to a change in ambient light or due to the presence of unusually light or dark objects (e.g., reflecting water body, metal roofs, asphalts, etc.). Certain applications of this invention involve aerial photography or surveillance. It is observed that aerial images of the ground usually contain plants and vegetation – which have more consistent reflectivity than water bodies or man-made structures such as roads and buildings. Of course, images of plants and vegetation are usually green-dominant (i.e., the green component is the greatest of the red, green and blue values). Therefore, intensity correlation can be made more accurate by focusing on the green-dominant pixels.

[0049] The exposure control module computes the average intensity of an image by selecting only green-dominant pixels. For example, if an image has 1 million pixels and 300,000 are

green-dominant, only those 300,000 green-dominant pixels are included in the calculation of average intensity. This results in an imaging process that is less susceptible to biasing caused by man-made structures and water bodies, whose pixels are usually not green-dominant. As previously noted, it is desirable to maintain an intensity value of about 127. When intensity value is over 127 (i.e., over-exposed), exposure time is reduced so that less light is captured. Similarly, when intensity value is under 127 (i.e., under-exposed), exposure time is increased so that more light is captured. For example, consider a system flying over a target terrain area having many white roofs, whose intensities are very high. Average intensity for the images captured would tend to be high. In most conventional systems, exposure time would be reduced in order to compensate. In such an example, however, reducing exposure time is not proper, because the average intensity of the images has been biased by the bright roofs. Reducing exposure time would result in images where the ground is darker than it should be. In contrast, if only green-dominant pixels are processed in accordance with the present invention, then pixels representing the overly bright roofs do bias the average intensity and the exposure time is not changed.

**[0050]** Thus, the exposure control module reduces intensity differences between input images. Nonetheless, further processing is provided to enhance tonal balance. There are a number of factors (e.g., lens physics, atmospheric conditions, spatial/positional relationships of imaging devices) that cause an uneven reception of light from the image plane. More light is received in the center of a camera or sensor than at the edges.

[0051] The mosaicing module of the present invention addresses this with an anti-vignetting function, illustrated in reference now to Figure 5. A number of focal columns 500, 502, 504, 506 and 508 converge from image plane 509 and cross through focal point 510 as they range across imaging target area 512 (e.g., ground terrain). Columns 500 through 508 may comprise individual resolution columns of a single camera or sensor, or may represent the focal axes of a number of independent cameras or sensors. For reference purposes, column 504 serves as the axis and point 513 at which column 504 intersects image plane 509 serves as a principal point. The exposure control module applies an anti-vignetting function multiplying the original intensity of an input pixel with a column-dependent anti-vignetting factor. Because the receiving surface is represented as a plane with a coordinate system, each column will have a number of resolution rows (not shown). This relationship may be expressed, for a pixel  $p$  at column  $x$  and row  $y$ , as follows:

$$\langle \text{adjusted intensity} \rangle = \langle \text{original intensity} \rangle * f(x);$$

where  $f(x)$  is a function of the form:

$$f(x) = \cos(\text{off-axis angle}) ** 4.$$

The off-axis angle 514 is: zero for center column 504; larger for columns 502 and 506; and larger still for columns 500 and 508. The overall field of view angle 516 (FOVx angle) is depicted between columns 504 and 508.

[0052] The function  $f(x)$  can be approximated by a number of line segments between columns. For a point falling within a line segment between any given columns  $c1$  and  $c2$ , an adjustment factor is computed as follows:

$$\text{<adjustment factor for } c\text{>} = f(c1) + [f(c2) - f(c1) * (c - c1)/(c2 - c1)];$$

5 [0053] where  $f(c1)$  and  $f(c2)$  are the  $f$  function values of the off-axis angles at column  $c1$  and  $c2$ , respectively.

[0054] Each set of input images needs to be stitched into a mosaic image. Even though the exposure control module regulates the amount of light each camera or sensor receives, the resulting input images may still differ in intensity. The present invention provides an intensity-  
10 balancing module that compares overlapping area between adjacent input images, to further balance the relative intensities. Because adjoining input images are taken simultaneously, the overlapping areas should, in theory, have identical intensity in both input images. However, due to various factors, the intensity values are usually not the same. Some such factors causing intensity difference could include, for example, the exposure control module being biased by  
15 unusually bright or dark objects present in the field of view of only a particular camera, or the boresight angles of cameras being different (i.e., cameras that are more slanted receive less light than those more vertical).

[0055] To balance two adjacent images, one is chosen as the reference image and the other is the secondary image. A correlation vector ( $fR$ ,  $fG$ ,  $fB$ ) is determined using, for example, the  
20 following process. Let  $V$  be a  $3 \times 1$  vector representing the values ( $R$ ,  $G$  and  $B$ ) of a pixel:

$$V = \begin{pmatrix} R \\ G \\ B \end{pmatrix}.$$

5 A correlation matrix C may be derived as:

$$C = \begin{pmatrix} FR & 0 & 0 \\ 0 & FG & 0 \\ 0 & 0 & FB \end{pmatrix};$$

10

where  $FR = AvgIr/AvgIn$ ;  $AvgIr$  = Red average intensity of overlapped region in reference image;  $AvgIn$  = Red average intensity of overlapped region in new image; and  $FG$  and  $FB$  are similarly derived.

[0056] The correlation matrix scales pixel values of the secondary image so that the average  
 15 intensity of the overlapping area of the secondary image becomes identical to the average intensity of the overlapping area of the reference image. The second image can be balanced to the reference image by multiplying its pixel values by the correlation matrix.

[0057] Thus, in one embodiment of a balancing process according to the present invention, a  
 center image is considered the reference image. The reference image is first copied to the  
 20 compound image (or mosaic). Overlapping areas between the reference image and an adjoining image (e.g., the near left image) are correlated to compute a balancing correlation matrix (BCM). The BCM will be multiplied with vectors representing pixels of the adjoining image to make the intensity of the overlapping area identical in both images. One embodiment of this relationship may be expressed as:

25 Let  $I(\text{center})$  = Average intensity of overlapping area in center image;

$I(\text{adjoining}) = \text{Average intensity of overlap in adjoining image; then}$

$\text{Balancing factor} = I(\text{center}) / I(\text{adjoining}).$

[0058] The balancing factor for each color channel (i.e., red, green and blue) is independently computed. These three values form the BCM. The now-balanced adjoining image is copied to the mosaic. Smooth transitioning at the border of the copied image is providing by “feathering” with a mask. This mask has the same dimension as the adjoining image and comprises a number of elements. Each element in the mask indicates the weight of the corresponding adjoining image pixel in the mosaic. The weight is zero for pixels at the boundary (i.e. the output value is taken from the reference image), and increases gradually in the direction of the adjoining image until it becomes unity – after a chosen blending width has been reached. Beyond the blending area, the mosaic will be entirely determined by the pixels of the adjoining image. Similarly, the overlaps between all the other constituent input images are analyzed and processed to compute the correlation vectors and to balance the intensities of the images.

[0059] A correlation matrix is determined using, for example, the following process with reference to Figure 6. Figure 6 depicts a strip 600 being formed in accordance with the present invention. A base mosaic 602 and a new mosaic 604, added along path (or track) 606, overlap each other in region 608. Let  $V$  be a vector that represents the R, G and B values of a pixel:

$$V = \begin{matrix} R \\ G \\ B \end{matrix}$$

Let  $h$  be the transition width of region 608, and  $y$  be the along-track 606 distance from the boundary 610 of the overlapped region to a point  $A$ , whose pixel values are represented by  $V$ .

Let  $C$  be the correlation matrix:

$$C = \begin{matrix} & \text{FR} & 0 & 0 \\ & 0 & \text{FG} & 0 \\ & 0 & 0 & \text{FB} \end{matrix}$$

The balanced value of  $V$ , called  $V'$  is:

$$V' = [y/h \cdot I + (1 - y/h) \cdot C] \times V, \text{ for } 0 < y < h;$$

$$V' = V, \text{ for } y \geq h;$$

Where  $I$  is the identity matrix

$$I = \begin{matrix} & 1 & 0 & 0 \\ & 0 & 1 & 0 \\ & 0 & 0 & 1 \end{matrix} .$$

Note that the “feathering” technique is also used in combination with the gradient to minimize seam visibility.

[0060] When mosaics are long, differences in intensity at the overlap may change from one end of the mosaic to the other. Computing a single correlation vector to avoid creating visible seams may not be possible. The mosaic can be divided into a number of segments corresponding to the position of the original input images that make up the mosaic. The process described above is applied to each segment separately to provide better local color consistency.

[0061] Under this refined algorithm, pixels at the border of two segments may create vertical seams (assuming north-south flight lines). To avoid this problem, balancing factors for pixels in this area have to be “transitioned” from that of one segment to the other. This is explained now with reference to Figure 7.

5 [0062] Figure 7 depicts a strip 700 being formed in accordance with the present invention. A base mosaic 702 and a new segment 704 overlap in area 706. Mosaic 702 and another new segment 708 overlap in area 710. Segments 704 and 708 overlap in area 712, and areas 706, 710 and 712 all overlap and coincide at area 714. For explanation purposes, point 716 serves as an origin for y-axis 718 and x-axis 720. Movement along y-axis 718 represents movement along  
10 the flight path of the imaging system. Point 716 is located at the lower left of area 714.

[0063] According to the present invention, the dimensions of a strip are determined by the minimum and maximum  $x$  and  $y$  values of the constituent mosaics. An output strip is initialized to a background color. A first mosaic is transferred to the strip. The next mosaic (along the flight path) is processed next. Intensity values of the overlapping areas of the new mosaic and  
15 the first mosaic are correlated, separately for each color channel. The new mosaic is divided into a number of segments corresponding to the original input images that made up the mosaic. A mask matrix, comprising a number of mask elements, is created for the new mosaic. A mask element contains the correlation matrix for a corresponding pixel in the new mosaic. All elements in the mask are initialized to unity. The size of the mask can be limited to just the  
20 transition area of the new mosaic. The correlation matrix is calculated for the center segment. The mask area corresponding to the center segment is processed. The values of the elements at

the edge of the overlap area are set to the correlation vector. Then, gradually moving away from the first mosaic along the strip, the components of the correlation matrix are either increased or decreased (whether they are less or more than unity, respectively) until they become unity at a predetermined transition distance. The area of the mask corresponding to a segment adjoining the center segment is then processed similarly. However, the area 814 formed by the first mosaic and the center and adjoining segments of the new image requires special treatment. Because the correlation matrix for the adjoining segment may not be identical to that of the center segment, a seam may appear at the border of the two segments in the overlap area 714 with the first mosaic. Therefore, the corner is influenced by the correlation matrices from both segments. For a mask cell A at distance  $x$  to the border with the center segment and distance  $y$  to the overlap edge, its correlation matrix is the distance-weighted average of the two segments, evaluated as follows:

For pixel A( $x$ ,  $y$ ) in area 714 at distance  $x$  to the border with the center segment, its balanced values are computed as the distance-weighted averages of the values computed using the two segments;

V1 is the balanced RGB vector based on segment 704;

V2 is the balanced RGB vector based on segment 708;

V' is the combined (final) balanced RGB vector

$$V' = ((d-x)/d).V1 + (x/d).V2;$$

Where

x-axis is the line going through bottom of overlapped region;

y-axis is the line going through the left side of the overlapped region between segments 704 and 708;

$h$  is the transition width; and

$d$  is the width of the overlapped region between segments 704 and 708.

5 The mask areas corresponding to other adjoining segments are computed similarly.

[0064] Further according to the present invention, a color fidelity (i.e., white-balance) filter is applied. This multiplies R and B components with a determinable factor to enhance color fidelity. The factor may be determined by calibrating the cameras and lenses. The color fidelity filter ensures that the colors in an image retain their fidelity, as perceived directly by the human  
10 eye. Within the image capture apparatus, the Red, Green and Blue light receiving elements may have different sensitivities to the color they are supposed to capture. A "while-balance" process is applied – where image of a white object is captured. Theoretically, pixels in the image of that white object should have equivalent R, G and B values. In reality, however, due to different sensitivities and other factors, the average color values for each R, G and B may be avgR, avgG  
15 and avgB, respectively. To equalize the color components, the R, G and B values of the pixels are multiplied by the following ratios:

R values are multiplied by the ratio  $\text{avgG} / \text{avgR}$ ; and

B values are multiplied by the ratio  $\text{avgG} / \text{avgB}$ .

The end result is that the image of the white object is set to have equal R G B components.

[0065] In most applications, a strip usually covers a large area of non-water surface. Thus, average intensity for the strip is unlikely to be skewed by anomalies such as highly reflecting surfaces. The present invention provides an intensity normalization module that normalizes the average intensity of each strip so that the mean and standard deviation are of a desired value.

5 For example, a mean of 127 is the norm in photogrammetry. A standard deviation of 51 helps to spread the intensity value over an optimal range for visual perception of image features. Each strip may have been taken in different lighting conditions and, therefore, may have different imaging data profiles (i.e., mean intensity and standard deviation). This module normalizes the strips, such that all have the same mean and standard deviation. This enables the strips to be  
10 stitched together without visible seams.

[0066] This intensity normalization comprises a computation of the mean intensity for each channel R, G and B, and for all channels. The overall standard deviation is then computed. Each R, G and B value of each pixel is transformed to the new mean and standard deviation:

$$\text{new value} = \text{new mean} + (\text{old value} - \text{old mean}) * (\text{new std}/\text{old std}).$$

15 [0067] Next, multiple adjacent strips are combined to produce tiled mosaics for an area of interest. Finished tiles can correspond to the USGS quads or quarter-quads. Stitching strips into mosaics is similar to stitching mosaics together to generate strips, with strips now taking the role of the mosaics. At the seam line between two strips, problems may arise if the line crosses elevated structures such as buildings, bridges, etc. This classic problem in photogrammetry  
20 arises from the parallax caused by the same object being looked at from two different

perspectives. During imaging of a building, for example, one strip may present a view from one side of the building while another strip presents a view from another side of the building. After the images are stitched together, the resulting mosaic may look like a tepee. In order to address this, a terrain-guided mosaicing process may be implemented to guide the placement of a seam line. For example, LIDAR or DEM data collected with, or analyzed from, image data may be processed to determine the configuration and shaping of images as they are mosaiced together. Thus, in some mosaiced images, a seam line may not be a straight line – instead comprising a seam line that shifts back and forth to snake through elevated structures.

**[0068]** Referring now to Figure 8, one embodiment of an imaging process 800 is illustrated in

accordance with the present invention as described above. Process 800 begins with a series 802 of one, or more, raw collected images. Images 802 are then processed through a white-balancing process 804, transforming them into a series of intermediate images. Series 802 is then processed through anti-vignetting function 806 before progressing to the orthorectification process 808. As previously noted, orthorectification may rely on position and attitude data 810 from the imaging sensor system or platform, and on DTM data 812. DTM data 812 may be developed from position data 810 and from, for example, USGS DTM data 814 or LIDAR data 816. Series 802 is now orthorectified and processing continues with color balancing 818. After color balancing, series 802 is converted by mosaicing module 820 into compound image 822. Module 820 performs the mosaicing and feathering processes during this conversion. Now, one or more compound images 822 are further combined in step 824, by mosaicing with a gradient and feathering, into image strip 826. Image strips are processed through intensity normalization

828. The now normalized strips 828 are mosaiced together in step 830, again by mosaicing with a gradient and feathering, rendering a finishing tiled mosaic 832. The mosaicing performed in step 830 may comprise a terrain-guided mosaicing, relying on DTM data 812 or LIDAR data 816.

5 [0069] Figure 9 illustrates diagrammatically how photos taken with the camera array assembly may be aligned to make an individual frame.

[0070] Figure 10 is a block diagram of the processing logic according to certain embodiments of the present invention. As shown in block diagram 1000, the processing logic accepts one or more inputs, which may include elevation measurements 1002, attitude measurements 1004  
10 and/or photo and sensor imagery 1006. Certain inputs may be passed through an initial processing step prior to analysis, as is shown in block 1008, wherein the attitude measurements are combined with data from ground control points. Elevation measurements 1002 and attitude measurements 1004 may be combined to generate processed elevation data 1010. Processed elevation data 1010 may then be used to generate elevation DEM 1014 and DTM 1016.  
15 Similarly, attitude measurements 1006 may be combined with photo and sensor imagery 1006 to generate georeferenced images 1012, which then undergo image processing 1018, which may include color balancing and gradient filtering.

[0071] Depending on the data set to be used (1020), either DTM 1016 or a USGS DEM 1022 is combined with processed images 1018 to generate orthorectified imagery 1024. Orthorectified  
20 imagery 1024 then feeds into self-locking flightlines 1026. Balancing projection mosaicing 1028 then follows, to generate final photo output 1030.

[0072] The present invention may employ a certain degree of lateral oversampling to improve output quality. Figure 11 is an illustration of a lateral oversampling pattern 1100 looking down from a vehicle according to certain embodiments of the present invention showing minimal lateral oversampling. In this illustration, the central nadir region 1102 assigned to the center camera overlaps only slightly with the left nadir region 1104 and right nadir region 1106, so that overlap is minimized. Figure 12 is an illustration of a lateral oversampling pattern 1200 looking down from a vehicle according to certain embodiments of the present invention showing a greater degree of lateral oversampling. In this illustration, the central nadir region 1202 shows a high degree of overlap with left nadir region 1204 and right nadir region 1206.

[0073] In addition to the use of lateral oversampling as shown in Figures 11 and 12, the present invention may employ flight line oversampling as well. Figure 13 is an illustration of a flight line oversampling pattern 1300 looking down from a vehicle according to certain embodiments of the present invention showing a certain degree of flight line oversampling but minimal lateral oversampling. Central nadir regions 1302 and 1304 are overlapped to one another along the flight line, but do not overlap laterally with left nadir regions 1306 and 1308 or with right nadir regions 1310 and 1312.

[0074] Figure 14 is an illustration of flight line oversampling looking down from a vehicle according to certain embodiments of the present invention showing significant flight line oversampling as well as significant lateral oversampling. It can be seen that each of the central nadir regions 1402-1406 are significantly overlapped with one another as well as with left nadir regions 1408-1412 and right nadir regions 1414-1418. Left nadir regions 1408-1412 are

overlapped with one another, as are right nadir regions 1414-1418. Accordingly, each point on the surface is sampled at least twice, and in some cases as many as four times. This technique uses the fact that in the area of an image that is covered twice, or more, by different camera sensors, a doubling of the image resolution is possible in both the lateral (across path) and flight line (along path) directions for an overall quadrupling of the resolution. In practice, the improvement in image/sensor resolution is somewhat less than doubled in each of the dimensions, approximately 40% in each dimension, or  $1.4 \times 1.4 = \sim 2$  times. This is due to the statistical variations of the sub-pixel alignment/orientation. In effect, the pixel grid is rarely exactly equidistant from the overlaid pixel grid. If extremely precise lateral camera sensor alignments were made at the sub-pixel level, a quadrupling of image resolution could be realized.

[0075] Figure 15 is an illustration of a progressive magnification pattern 1500 looking down from a vehicle according to certain embodiments of the present invention. Central nadir region 1502 is bounded on its left and right edges by inner left nadir region 1504 and inner right nadir region 1506, respectively. Inner left nadir region 1504 is bounded on its left edge by outer left nadir region 1508, while inner right nadir region 1506 is bounded on its right edge by outer right nadir region 1510. Note that these regions exhibit a minimal degree of overlap and oversampling from one to another.

[0076] Figure 16 is an illustration of a progressive magnification pattern 1600 looking down from a vehicle according to certain embodiments of the present invention. Central nadir region 1602 is bounded on its left and right edges by inner left nadir region 1604 and inner right nadir region 1606, respectively. Inner left nadir region 1604 is bounded on its left edge by outer left

nadir region 1608, while inner right nadir region 1606 is bounded on its right edge by outer right nadir region 1610. Note that, as above, these regions exhibit a minimal degree of overlap and oversampling from one to another. Within each of the nadir regions 1604-1610, there is a central image region 1614-1620 shown shaded in grey.

5   **[0077]**   Figure 17 is an illustration of a progressive magnification pattern 1700 looking down from a vehicle according to certain embodiments of the present invention. In the center of pattern 1700, a left inner nadir region 1702 and a right inner nadir region 1704 overlap in the center. A left intermediate nadir region 1706 and a right intermediate nadir region 1708 are disposed partly outside of regions 1702 and 1704, respectively, each sharing an overlapping area  
10   with the respective adjacent area by approximately 50%. An outer left nadir region 1710 and an outer right nadir region 1712 are disposed partly outside of regions 1706 and 1708, respectively, each sharing an overlapping area with the respective adjacent area by approximately 50%. A central image region 1714 is disposed in the center of pattern 1700, comprised of the central portions of nadir regions 1702-1712.

15   **[0078]**   Figure 18 depicts a schematic of the architecture of a system 1800 according to certain embodiments of the present invention. System 1800 may include one or more GPS satellites 1802 and one or more SATCOM satellites 1804. One or more GPS location systems 1806 may also be included, operably connected to one or more modules 1808 collecting LIDAR, GPS and/or X, Y, Z location data and feeding such information to one or more data capture system  
20   applications 1812. One or more data capture system applications 1812 may also receive spectral data from a camera array 1822. A DGPS 1810 may communicate with one or more SATCOM

satellites 1804 via a wireless communications link 1826. One or more SATCOM satellites 1804 may, in turn, communicate with one or more data capture system applications 1812.

[0079] One or more data capture system applications 1812 may interface with an autopilot 1816, an SSD and/or a RealTime StitchG system 1820, which may also interact with one  
5 another. SSD 1814 may be operably connected to RealTime DEM 1818. Finally, RealTime DEM 1818 and RealTime StitchG 1820 may be connected to a storage device, such as disk array 1824.

[0080] The modules, algorithms and processes described above can be implemented in a number technologies and configurations. Embodiments of the present invention may comprise  
10 functional instances of software or hardware, or combinations thereof. Furthermore, the modules and processes of the present invention may be combined together in a single functional instance (e.g., one software program), or may comprise operatively associated separate functional devices (e.g., multiple networked processor/memory blocks). All such implementations are comprehended by the present invention.

15 [0081] The embodiments and examples set forth herein are presented to best explain the present invention and its practical application and to thereby enable those skilled in the art to make and utilize the invention. However, those skilled in the art will recognize that the foregoing description and examples have been presented for the purpose of illustration and example only. The description as set forth is not intended to be exhaustive or to limit the  
20 invention to the precise form disclosed. Many modifications and variations are possible in light of the above teaching without departing from the spirit and scope of the following claims.